


6181Y

PVC Insulated and Sheathed Single Core Cable. BS 6004. 300/500 V



Prysmian 6181Y is a low voltage single core, PVC insulated copper conductor with an additional PVC oversheath insulation for physical protection

KEY APPLICATIONS

Fixed installation in dry or damp premises on walls, boards or trays, in channels or embedded in plaster

FEATURES AND BENEFITS

- Manufactured under ISO 9001 Quality management systems

STANDARDS



BS 6004

BS EN 60332-1-2

Construction Standard

Flame Propagation - Single Cable

CONSTRUCTION

Conductor material	Copper
Conductor surface	Bare
Core insulation material	Polyvinyl chloride (PVC)
Material outer sheath	Polyvinyl chloride (PVC)
Cable shape	Round

APPLICATIONS PROPERTIES

Nominal voltage U ₀ [V]	300
Nominal voltage U [V]	500
Flame retardant	In accordance with BS EN 60332-1-2
Max. conductor temperature [°C]	70
Min. Operation temperature [°C]	-15
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	60
Bending radius (rule)	4D

COLOURS

Insulation:
Brown or Blue

Sheath:
Grey

CURRENT RATINGS

Refer to table 4D1 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations

CONTACT INFORMATION

Prysmian Cables & Systems Limited, Chickenhall Lane, Eastleigh, Hampshire, SO50 6YU, United Kingdom
uk.prysmiangroup.com
www.whyprysmian.co.uk

Copyright Prysmian Group - 2021

You may not reproduce the content, either wholly or in part, of this Datasheet, without the express permission of the copyright owner.

Prysmian Group reserves the right to amend the information within this Datasheet without prior notice. This Datasheet may include inaccuracies, omissions of content and of information. Please verify with the Prysmian UK Technical team, all information contained in this technical datasheet when placing an order.

TECHNICAL DATA

Nominal cross section conductor [mm ²]	Conductor category	Nominal thickness insulation [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
1	Class 1 = solid	0.7	4	27	18.1
1.5	Class 1 = solid	0.7	4.5	35	12.1
2.5	Class 1 = solid	0.8	5.1	48	7.41
4	Class 2 = stranded	0.8	6.1	71	4.61
6	Class 2 = stranded	0.8	6.6	93	3.08
10	Class 2 = stranded	1	7.8	145	1.83
16	Class 2 = stranded	1	9	210	1.15
25	Class 2 = stranded	1.2	10.9	320	0.727
35	Class 2 = stranded	1.2	12	420	0.524